


PROFLET 30™

WE'VE GOT YOU COVERED.



TECHNICAL DATA SHEET



SPECIFICATIONS	ProFelt 30	30# Felt
Width x Length / Roll	4 ft x 250 ft	3 ft x 72 ft
Weight / Roll	28 lbs	60 lbs
Coverage	Approx. 950 ft / Roll*	Approx. 216 ft / Roll*
Rolls / Pallet	49 Rolls	30 Rolls
Pallet Weight	1412 lbs	1800 lbs
PROPERTIES	ProFelt 30	TEST METHOD
Basis Weight-Roll Weight	4.0 oz/yd ² (+/-5%) - 2.8 lbs/square	-
Permeability	0.05 perms	ASTM E96
Water Transmission	PASS	ASTM D4869
Tensile Strength (MD/CD)	100 lbs / 80 lbs	ASTM D751
Tear Strength (MD/CD)	42 lbs / 40 lbs	ASTM D4533
Elongation (MD/CD)	18% / 15%	ASTM D751
Water Ponding	PASS	AC48 Sec. 4.4
UV Weathering	180 Days	-
Class A Fire Resistance	UL 790, UBC 15-2	ASTM E108
Temperature Range	-70° F to 300° F	-

*Approximate 950 sq ft per roll or less depending upon overlap and roof design. Values are typical data and not limiting specifications. All values +/- 7%. Consult technical representative. Effective temperature range -40°F to 265°F.

Meets or exceeds testing standards ICC-ES AC 188, ASTM D226, and ASTM D4869.

SAFETY PRECAUTIONS - ProFelt 30™

Read before use. Refer to MSDS for additional information.

Always follow good roofing practices. Comply with all OSHA or other standards & codes for roof work. Always use a Fall Protection System when working on roofs. **ProFelt 30** may be slippery when wet or covered with mud, dust, frost, ice or snow. Use roof jacks with planks, toe boards or storage platforms secured to the substrate to prevent slippage of stored material. Stay away from power lines; do not contact with body or equipment. On steep pitched surfaces, roof jacks with planks should be used for standing. Follow all ladder safety standards and codes. Never leave scraps, wrappers or other debris on the roof surface. Dispose of waste in accordance with local regulations.

DISCLAIMER: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma "R" Products' control are such that Perma "R" Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the user's responsibility to determine the suitability of any material for specific purposes and to adopt such safety precautions as may be necessary.



PRP_PFT30-TDS_06-25

permarproducts.com | 800-647-6130 | 2604 Sunset Drive | Grenada, MS 38901

© 2025 Perma "R" Products, Inc. | Member of INDEVCO North America