



PERMA “R” PRODUCTS

WE’VE GOT YOU COVERED.

TECHNICAL DATA SHEET



CHOOSE YOUR WRAP

SPECIFICATIONS	PermaPro®	PermaWrap®
Composition	Woven Micro-Perforated Polypropylene	Woven Micro-Perforated Polypropylene
Weight	1.9 oz.yd ² (+/-5%)	2.2 oz.yd ² (+/-5%)
Thickness	Avg 5.0 mils	Avg 6.5 mils
Tensile Strength	MD 53 lb • CD 44 lb	MD 80 lb • CD 40 lb
Tear Strength	MD 21 lb • CD 19 lb	MD 40 lb • CD 13 lb
Water Resistance	PASS	PASS
MTVR/Perms	12–15 perms	12–15 perms
UV Resistance	9 months	9 months
Fire Rating	Class A	Class A
Code Listing	CCRR-0459	CCRR-0459

AVAILABLE SIZES

*3' x 100'	*3' x 150'	*3' x 195'
*4.5' x 100'	*4.5' x 150'	*4.5' x 195'
9' x 100'	9' x 150'	9' x 195'
10' x 100'	10' x 150'	10' x 195'

PermaPro® House Wrap | PermaWrap® House Wrap

FOR USE AS A REPLACEMENT FOR GRADE D PAPER AS A WATER RESISTIVE AND AIR INFILTRATION BARRIER.

Meets the following certifications: Complies with ICC-ES AC308 “Water-Resistive Barriers/Weather Barriers”.
ICC report No. ESR-254

*Call for quote.

DISCLAIMER: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma “R” Products’ control are such that Perma “R” Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the user’s responsibility to determine the suitability of any material for specific purposes and to adopt such safety precautions as may be necessary.

PRP_HW-TDS_07-24



permarproducts.com | 800-647-6130 | 2604 Sunset Drive | Grenada, MS 38901

© 2024 Perma “R” Products, Inc. | Member of INDEVCO North America