

PROTAK™ STRETCH

WE'VE GOT YOU COVERED.

TECHNICAL DATA SHEET



Perma "R" Product's ProTAK™ Stretch flashing tape is a butyl window and door flashing designed to bring you all the benefits of a non-asphalt tape. When installed according to specifications shown in our flashing system installation guide, ProTAK will protect against water penetration into the building envelop, preventing costly and unhealthy mold and mildew growth or rot. It is used almost exclusively for building envelope applications and exceeds all current AAMA 711 standards.

ProTAK™ Stretch Flashing Tape

- Stretches more than double to conform to curves and corners eliminating need for corner flashing patches at window sides
- Slow acting adhesive for easy repositioning
- Superior adhesion to wood, aluminum, vinyl, rigid board insulation, and other common building materials

PROPERTIES	SPECIFICATIONS
Adhesive Composition	Butyl Rubber
Thickness	50 mil
Installation Temp Range	40° F - 180° F
Operating Temp Range	-30° F - 200° F
Nail Sealability	PASS
Tensile Strength	>400 to 295 PSI
Water Vapor Trans Rate	<0.2 g/100in ² /24 hrs
UV Exposure	Up to 12 Months
Shelf Life	36 Months
Warranty	20-year System Limited Lifetime

Recommended Storage Conditions: 60-80°F at 40-60% RH

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma "R" Products' control are such that Perma "R" Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for specific purpose and to adopt such safety precautions as may be necessary.



Application Information: Ensure all involves surfaces are clean, dry and free of oil and moisture. Exercise care during application to prevent air, moisture, or contaminant entrapment. ProTAK features a strong, flexible backing.

Packaging and Handling: Do not open until ready for use in order to maximize shelf life. Store at 60° F - 80° F. This Product is available in standard roll widths of 6" and 9". Standard roll length is 75 feet. Custom sizing is also available.

- Easy to remove release liner
- Self-healing after puncture
- Compatible with sealants and caulking
- Free of asphalts, VOCs, and solvents
- Meets AAMA 711

SIZE	ROLLS PER CASE	CASES PER PALLET	Part #
6" x 75'	1	45	75601
9" x 75'	1	45	75901



PRP_PROTAK-TDS_07-24

permarproducts.com | 800-647-6130 | 2604 Sunset Drive | Grenada, MS 38901

© 2024 Perma "R" Products, Inc. | Member of INDEVCO North America